

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1-28 (cancelled).

29. (currently amended) A method of inserting an artificial implant into a disc space between two adjacent vertebral bodies, the method comprising ~~the steps of:~~
- providing an artificial implant having an upper surface and a lower surface, the upper and lower surfaces being at least arcuate in part along ~~a~~ a plane transverse to a mid-longitudinal axis of the implant and adapted to contact an adjacent vertebral body, the implant having a lateral side and an opposite medial side and a maximum width therebetween, the implant having generally non-linear leading and trailing ends, ~~the implant having a longitudinal axis parallel to the mid-longitudinal axis of the implant and passing through said~~ leading and trailing ends, the mid-longitudinal axis being perpendicular to and bisecting the maximum width into two equal parts, the trailing end being configured to generally conform to at least a portion of the natural anatomical curvature of at least one of the anterior, posterior, and lateral aspects of the vertebral bodies, the implant having a length between the leading and trailing ends adapted to allow at least a portion of the implant proximate the leading end and at least a portion of the implant proximate the trailing end to each overlie respective portions of a peripheral rim of the densely compacted bone of the apophyseal rim along the anatomical curvature of the adjacent vertebral bodies when the implant is implanted in the disc space;
 - forming an opening across a height of the disc space and into a portion of each of the adjacent vertebral bodies, the opening in the portion of each of the adjacent vertebral bodies being at least in part curved;
 - inserting the implant into the opening with the lateral side of the implant facing one of the anterior and lateral aspects of the vertebral bodies;

positioning the leading end of the implant so that at least a portion of the implant proximate the leading end between the medial side and the mid-longitudinal axis overlies the apophyseal rim without substantially protruding from the spine; and

positioning the trailing end of the implant so that at least a portion of the implant proximate the trailing end between the medial side and the mid-longitudinal axis overlies the apophyseal rim when said at least a portion of the implant proximate the leading end overlies the apophyseal rim without substantially protruding from the spine.

30. (currently amended) The method of claim 29, further comprising ~~the step of~~ attaching a driver instrument to the implant to insert the implant into the opening formed during the step of forming. \
31. (currently amended) The method of claim 29, wherein the implant is a fusion implant having a hollow therein, further comprising ~~the step of loading the~~ implant with a fusion promoting material prior to ~~the step of inserting the implant.~~
32. (original) The method of claim 31, wherein the fusion promoting material includes at least one of bone, coral, bone morphogenetic protein, and genes coding for the production of bone.
33. (currently amended) The method of claim 29, further comprising ~~the step of~~ combining the implant with a fusion promoting material.
34. (original) The method of claim 33, wherein the fusion promoting material includes at least one of bone, coral, bone morphogenetic protein, and genes coding for the production of bone.
35. (currently amended) The method of claim 29, wherein the ~~step of forming of the~~ opening includes ~~the sub-step of drilling the opening.~~
36. (currently amended) The method of claim 29, wherein the ~~step of inserting of the~~ implant includes linearly inserting the implant into the opening.
37. (currently amended) The method of claim 29, wherein the ~~step of inserting of the~~ implant includes rotating the implant into the opening.
38. (currently amended) The method of claim 29, wherein the ~~step of inserting of the~~ implant includes screwing the implant into the opening.

39. (currently amended) A method of inserting a pair of artificial implants into a disc space between two adjacent vertebral bodies, the method comprising the steps of:

providing a first artificial implant having generally non-linear leading and trailing ends, the trailing end being configured to generally conform to at least a portion of the natural anatomical curvature of at least one of the anterior, posterior, and lateral aspects of the vertebral bodies, the first implant having a lateral side and an opposite medial side and a maximum width therebetween less than one half of the width of the disc space, the implant having a ~~longitudinal axis parallel to the mid-longitudinal axis and passing through said~~ leading and trailing ends, the mid-longitudinal axis being perpendicular to and bisecting the maximum width into two equal parts, and a length between the leading and trailing ends adapted to allow at least a portion of the implant proximate the leading end and at least a portion of the implant proximate the trailing end to each overlie a peripheral rim of the densely compacted bone of the apophyseal rim along the anatomical curvature of the adjacent vertebral bodies when the first implant is implanted in the disc space;

providing a second artificial implant having generally non-linear leading and trailing ends being configured to generally conform to at least a portion of the natural anatomical curvature of at least one of the anterior, posterior, and lateral aspects of the vertebral bodies, the second implant having a lateral side and an opposite medial side and a maximum width therebetween less than one half of the width of the disc space, the implant having a ~~longitudinal axis parallel to the mid-longitudinal axis and passing through said~~ leading and trailing ends, the mid-longitudinal axis being perpendicular to and bisecting the maximum width into two equal parts, and a length between the leading and trailing ends adapted to allow at least a portion of the implant proximate the leading end and at least a portion of the implant proximate the trailing end to each overlie the peripheral rim of the densely compacted bone of the apophyseal rim along the

anatomical curvature of the adjacent vertebral bodies when the second implant is implanted in the disc space;

forming at least one opening across a height of the disc space and into a portion of each of the adjacent vertebral bodies, the at least one opening in the portion of each of the adjacent vertebral bodies being at least in part curved;

inserting the first implant into the at least one opening with the lateral side facing one of the anterior and lateral aspects of the vertebral bodies;

inserting the second implant into the at least one opening with the lateral side facing one of the anterior and lateral aspects of the vertebral bodies;

positioning the leading end of each implant so that at least a portion of the implant proximate the leading end between the medial side and the mid-longitudinal axis overlies the apophyseal rim without substantially protruding from the spine; and

positioning the trailing end of each implant so that at least a portion of the implant proximate the trailing end between the medial side and the mid-longitudinal axis overlies the apophyseal rim when the at least a portion of the implant proximate the leading end overlies the apophyseal rim without substantially protruding from the spine.

40. (currently amended) The method of claim 39, wherein the providing of at least one of the implants~~said providing steps~~ includes providing an implant with an asymmetrical trailing end.
41. (currently amended) The method of claim 29, wherein the~~said~~ providing of the implant~~step~~ includes providing an implant with a symmetrical trailing end.
42. (currently amended) The method of claim 39, wherein each implant is a fusion implant having a hollow therein, further comprising ~~the step of loading each~~ implant with fusion promoting material prior to ~~the steps of inserting each~~ implant.
43. (original) The method of claim 42, wherein the fusion promoting material includes at least one of bone, coral, bone morphogenetic protein, and genes coding for the production of bone.

44. (currently amended) The method of claim 39, further comprising ~~the step of~~ combining at least one of the implants with a fusion promoting material.
45. (original) The method of claim 44, wherein the fusion promoting material includes at least one of bone, coral, bone morphogenetic protein, and genes coding for the production of bone.
46. (currently amended) The method of claim 39, wherein the ~~step of forming of the opening~~ includes ~~the sub-step of drilling the~~ at least one opening.
47. (currently amended) The method of claim 39, wherein each of ~~the steps of inserting~~insertion includes linearly inserting the implant into the at least one opening.
48. (currently amended) The method of claim 39, wherein each of ~~the steps of inserting~~insertion includes rotating the implant into the at least one opening.
49. (currently amended) The method of claim 39, wherein each of ~~the steps of inserting~~insertion includes screwing the implant into the at least one opening.
50. (currently amended) The method of claim 29, wherein the ~~step of positioning of the implant~~ includes positioning a majority of the trailing end of the implant along the apophyseal rim of at least one of the adjacent vertebral bodies.
51. (currently amended) The method of claim 29, wherein the ~~step of providing of the implant~~ includes providing the trailing end of the implant with a curved portion generally corresponding to the natural curvature of at least one of the anterior and lateral aspects of the vertebral bodies.
52. (currently amended) The method of claim 39, wherein the ~~step of positioning of each implant~~ includes positioning a majority of the trailing end of each implant along the apophyseal rim of at least one of the adjacent vertebral bodies.
53. (currently amended) The method of claim 39, wherein the ~~step of providing of at least one of the implants~~ includes providing the trailing end of at least one of the implants with a curved portion generally corresponding to the natural curvature of at least one of the anterior and lateral aspects of the vertebral bodies.
54. (currently amended) The method of claim 29, wherein the ~~positioning step of the implant~~ includes ~~the sub-step of positioning the entire trailing end of the implant~~

- on the peripheral rim of the densely compacted bone along the anatomical curvature of the adjacent vertebral bodies.
55. (currently amended) The method of claim 39, wherein the positioning of each implant~~step~~ includes ~~the sub-step of positioning~~ the entire trailing end of each implant on the peripheral rim of the densely compacted bone along the anatomical curvature of the adjacent vertebral bodies.
56. (currently amended) The method of claim 29, wherein the positioning of the implant~~step~~ includes ~~the sub-step of positioning~~ at least a portion of the trailing end of the implant between the medial side and the mid-longitudinal axis of the implant on at least one of the anterior cortex and apophyseal rim of the adjacent vertebral bodies.
57. (currently amended) The method of claim 39, wherein the positioning of each implant~~step~~ includes ~~the sub-step of positioning~~ at least a portion of the trailing end of each implant between the medial side and the mid-longitudinal axis of the implant on at least one of the anterior cortex and apophyseal rim of the adjacent vertebral bodies.
58. (currently amended) The method of claim 29, wherein the ~~step of providing~~ of the implant includes ~~the sub-step of providing~~ the implant with a first maximum length measured along the medial side that is longer than a second maximum length measured along the lateral side.
59. (currently amended) The method of claim 39, wherein the ~~step of providing~~ of each implant includes ~~the sub-step of providing~~ eachthe implant with a first maximum length measured along the medial side that is longer than a second maximum length measured along the lateral side.
- Claims 60 and 61 (cancelled).
62. (new) The method of claim 29, wherein the providing of the implant includes providing the implant with at least in part arcuate upper and lower surfaces extending from the lateral side to the medial side of the implant.

63. (new) The method of claim 29, wherein the providing of the implant includes providing the implant with upper and lower surfaces each having an arcuate portion extending across the mid-longitudinal axis of the implant.
64. (new) The method of claim 29, wherein the providing of the implant includes providing the implant with each of the upper and lower surfaces including at least one opening adapted to communicate with one of the adjacent vertebral bodies, the openings in the upper and lower surfaces being in communication with one another and adapted to permit for the growth of bone from adjacent vertebral body to adjacent vertebral body through the implant.
65. (new) The method of claim 39, wherein each of the implants provided include upper and lower surfaces that are each arcuate along a vertical plane transverse to the mid-longitudinal axis of each respective implant.
66. (new) The method of claim 39, wherein each of the implants provided include upper and lower surfaces that each include an arcuate portion extending from the lateral side to the medial side of each respective implant.
67. (new) The method of claim 39, wherein each of the implants provided include upper and lower surfaces that have an arcuate portion extending across the mid-longitudinal axis of each respective implant.
68. (new) The method of claim 39, wherein each of the implants provided include upper and lower surfaces that include at least one opening adapted to communicate with one of the adjacent vertebral bodies, the openings in the upper and lower surfaces being in communication with one another and adapted to permit for the growth of bone from adjacent vertebral body to adjacent vertebral body through each respective implant.